

Stormy Pro

STORMY PRO is an evolution of our belt driven professional piston compressors that brings even more features, and efficiency to our product range.

Wheeled models 11 bar












Available in a mix of:

- Four sizes from 2 to 5,5 HP
- Four tank sizes up to 200 litres tank
- Two types of electric supplies.

It includes following features:

- ON/OFF pressure switch for easy control
- Pressure reducer to adjust desired outlet pressure
- Handle and wheels (including jockey wheel) for easy transport
- Steel fan guard for protection
- Cast iron cylinders for improved cooling
- After cooler for reduced air temperature.

TECHNICAL DATA

TYPE														
			litre	bar	psi	l/min	cfm	HP			kW	rpm	V/Hz/Ph	
25C2MYPRO	1 NS11S	27	11	159	254	9	2	1,5	1250	230/50/1	805	355	630	43
25C2YPRO	1 NS11S	27	11	159	254	9	2	1,5	1250	400/50/3	805	355	630	43
50C2MYPRO	1 NS11S	50	11	159	254	9	2	1,5	1250	230/50/1	840	395	710	52
50C2YPRO	1 NS11S	50	11	159	254	9	2	1,5	1250	400/50/3	840	395	710	52
90C2MYPRO	1 NS11S	90	11	159	254	9	2	1,5	1250	230/50/1	970	485	835	63
90C2YPRO	1 NS11S	90	11	159	254	9	2	1,5	1250	400/50/3	970	485	835	63
90C3MYPRO	1 NS18S	90	11	159	387	13,7	3	2,2	1100	230/50/1	970	485	890	66
90C3YPRO	1 NS18S	90	11	159	387	13,7	3	2,2	1100	400/50/3	970	485	890	66
200C3MYPRO	1 NS18S	200	11	159	387	13,7	3	2,2	1100	230/50/1	1400	560	890	100
200C3YPRO	1 NS18S	200	11	159	387	13,7	3	2,2	1100	400/50/3	1400	560	890	100
200C4YPRO	2 NS29S	200	11	159	514	18,1	4	3	1400	400/50/3	1400	560	1000	112
200C5,5YPRO	2 NS39	200	11	159	653	23,1	5,5	4	1000	400/50/3	1425	560	1210	120

Other voltages available upon request