

Bluewind

BLUEWIND range has been developed to ensure quality, reliability and efficiency for semi professional applications requiring standard duty and occasional use of compressed air. Portable or mobile, they can easily fit in a car and will give full satisfaction to hobbyists, craftsmen and artisans.


Coaxial 8 bar



These 2 HP models have a maximum outlet pressure of 8 bar, are available in three tank sizes and include the following features:

- ON/OFF pressure switch
- Pressure reducer
- Carrying handle (6 litres) and wheels (24 and 50 litres).

TECHNICAL DATA

TYPE														
		litre	bar	psi	l/min	cfm	HP	kW	rpm	V/Hz/Ph	L	W	H	Kg
6DP2	1 FC 2	6	8	116	222	7,8	2	1,5	2850	230/50/1	440	460	450	20
25DC2	1 FC 2	24	8	116	222	7,8	2	1,5	2850	230/50/1	585	280	580	24
50DC2	1 FC 2	50	8	116	222	7,8	2	1,5	2850	230/50/1	780	390	650	34


Belt Driven 9 bar



These 2 HP models have a maximum outlet pressure of 9 bar, are available in three tank sizes and include the following features:

- ON/OFF pressure switch
- Pressure reducer
- Handle, wheels and pad
- Plastic belt guard for protection and improved cooling.

TECHNICAL DATA

TECHNICAL DATA														
TYPE														
		litre	bar	psi	l/min	cfm	HP	kW	rpm	V/Hz/Ph	L	W	H	Kg
25BC2	1 B2800I	27	9	130	254	9	2	1,5	1500	230/50/1	820	355	655	41
50BC2	1 B2800I	50	9	130	254	9	2	1,5	1500	230/50/1	840	395	730	44
90BC2	1 B2800I	90	9	130	254	9	2	1,5	1500	230/50/1	970	490	850	56