

Bluewind Pro

BLUEWIND PRO range has been designed to offer a direct driven solution to small but heavier duty requirements, while maintaining a compact design normal operating and service costs.


Coaxial 8 bar



These 2 HP and 8 bar models, are available in five tank sizes and include the following features:

- Aluminium block with large fins for improved cooling
- ON/OFF pressure switch
- Pressure reducer
- Carrying handle (6 litres), wheels and pad (10 to 90 litres).

TECHNICAL DATA

TYPE									
		litre	bar psi	l/min cfm	HP kW	rpm	V/Hz/Ph	L W H	Kg
6DM2PRO	1 F 241	6	8 116	240 8,4	2 1,5	2850	230/50/1	440 460 450	19
10DM2PRO	1 F 241	10	8 116	240 8,4	2 1,5	2850	230/50/1	380 355 640	19
25DM2PRO	1 F 241	24	8 116	240 8,4	2 1,5	2850	230/50/1	585 280 585	22
50DM2PRO	1 F 241	50	8 116	240 8,4	2 1,5	2850	230/50/1	780 390 660	32
100DM2PRO	1 F 241	90	8 116	240 8,4	2 1,5	2850	230/50/1	970 455 800	43

Coaxial 10 bar


These 3 HP and 10 bar models, are available in two variants and includes the following features:

- V design block
- ON/OFF pressure switch
- Pressure reducer with filter and direct outlet
- Carrying handle (6 litres), wheels and pad (2*11 litres).

2*11 model has been designed with inflatable wheels and extendible handle to ensure easy transport even outdoor. It includes a protecting frame and a anti-slippery tray to store tools.



TECHNICAL DATA

TYPE									
		litre	bar psi	l/min cfm	HP kW	rpm	V/Hz/Ph	L W H	Kg
25DM3PRO	1 GV 34	24	10 145	340 12	3 2,2	1450	230/50/1	625 555 785	44
2*11DM3PRO	1 GV 34	2*11	10 145	340 12	3 2,2	1450	230/50/1	810 625 615	56