

High-pressure nitrogen skid

PPNG 1-12 skid HE



Meet Pneumatech's all-in-one high-pressure nitrogen solution. The PPNG skid HE is the complete on-site nitrogen generation system that frees you from dependency on external suppliers. The PPNG skid HE comes in two versions: 40-bar for peak and on-demand nitrogen and 300-bar with bottle storage. Each comes in different sizes to meet your specific needs. Supremely easy to install and operate, the PPNG skid HE ensures an always dependable nitrogen supply while significantly lowering your operational costs.

An all-in-one N₂ solution

The PPNG skid HE combines all components of a nitrogen generation system on one sturdy base frame: a VSD compressor, a high-pressure booster, a PSA nitrogen generator, and all necessary air and nitrogen storage and treatment. No need to specify, integrate, and commission all these separate components. Instead, you get a complete plug-and-play system with just one power supply and one nitrogen connection to manage.

Features and benefits:

- All-in-one solution with all components built-in and piped together
- Single power supply for the complete skid
- 30% more efficient than other high-pressure N₂ packages
- All components are built and tested to work together optimally
- 40-bar and 300-bar version in different sizes and with a wide range of options
- VSD compressor delivers double-digit energy savings and emissions reductions
- 40 or 300-bar booster sized to minimize power use
- High-efficiency PSA generator with purity selection up to 99.999%
- Additional filtration is built in as standard to protect critical N₂ applications
- Optimal control, monitoring and connectivity thanks to Purelogic™ Controller
- Forklift slots for easy lifting and moving

General Specifications

- Purity range: 99.95% to 99.999%*
- Outlet pressures available: 40 barg and 300 barg**
- Ambient temperature range: 5-50°C/41-122°F***
- Power supply: 400/3/50 (460/3/60 available upon request)

* Lower purities available upon request

** Different pressures available upon request

*** Above 35°C applications an oversized refrigerant dryer should be selected

A complete nitrogen system

PPNG HE nitrogen generator: Efficient performance and guaranteed nitrogen purity up to 99.999%.

Purelogic™ controller: Optimal control and easy local and remote monitoring.

4-stage inlet filtration: Guaranteed air quality safeguards the N₂ generator and user applications.

Variable speed drive compressor with integrated refrigerant dryer: Guaranteed stable supply of pressure with double-digit reductions in energy use and emissions.



40 barg receiver or 300 barg cylinder nitrogen storage: Bottle rack with up to 16 high-pressure cylinders or a 40 barg receiver help manage peak demands by providing stored N₂.

40 barg or 300 barg nitrogen booster: Sized to minimize power consumption and number of start/stops.

Additional filtration: Removes contaminants for sensitive applications.

Local control panel and distribution board: One panel to power and control the complete system.

Technical specifications for PPNG skid HE

Pneumatech variant	PPNG Skid 1 HE	PPNG Skid 2 HE	PPNG Skid 3 HE	PPNG Skid 4 HE	PPNG Skid 5 HE	PPNG Skid 6 HE	PPNG Skid 7 HE	PPNG Skid 8 HE	PPNG Skid 9 HE	PPNG Skid 10 HE	PPNG Skid 11 HE	PPNG Skid 12 HE
N ₂ pressure - Nominal	40	40	40	40	40	40	300	300	300	300	300	300
N ₂ capacity - 99.95%	8.9	14.0	21.6	31.5	36.9	73.8	9.9	14.9	24.0	36.0	38.0	80.4
N ₂ capacity - 99.99%	6.6	10.4	20.6	30.3	36.9	73.8	7.3	11.1	22.9	32.9	38.0	80.4
N ₂ capacity - 99.999%	4.1	6.3	13.6	20.4	27.2	49.7	4.5	6.9	15.1	22.4	29.0	55.2
Compressor model	8 kw	11 kw	15 kw	22 kw	31 kw	45 kw	8 kw	8 kw	15 kw	19 kw	22 kw	45 kw
Inlet filtration	PMH G - C - VT - D	PMH G - C - VT - D	PMH G - C - VT - D	PMH G - C - VT - D	PMH G - C - VT - D	PMH G - C - VT - D	PMH G - C - VT - D	PMH G - C - VT - D	PMH G - C - VT - D	PMH G - C - VT - D	PMH G - C - VT - D	PMH G - C - VT - D
Air / N ₂ buffer vessels (Litres)	500	500	1000	1000	1500	2000	500	500	1000	1000	1500	2000
Nitrogen generator	PPNG12 HE	PPNG18 HE	PPNG37 HE	PPNG50 HE	PPNG75 HE	PPNG100 HE	PPNG12 HE	PPNG18 HE	PPNG37 HE	PPNG50 HE	PPNG75 HE	PPNG100 HE
Nitrogen LP storage	1000	1000	1000	1500	1000	2000	1000	1000	1000	1000	1000	1000
Nitrogen booster	7.5 kw	7.5 kw	7.5 kw	7.5 kw	7.5 kw	7.5 kw	5.5 kw	5.5 kw	5.5 kw	11 kw	11 kw	2x11 kw
HP filtration	50 Barg G - C - V - D	50 Barg G - C - V - D	50 Barg G - C - V - D	50 Barg G - C - V - D	50 Barg G - C - V - D	50 Barg G - C - V - D	HP V filter	HP V filter	HP V filter	HP V filter	HP V filter	HP V filter
HP storage	45 Barg 500L	45 Barg 500L	45 Barg 1000L	45 Barg 1000L	45 Barg 1000L	45 Barg 1000L	12 x 50L X 300 Barg	12 x 50L X 300 Barg	12 x 50L X 300 Barg	16 x 50L x 300 Barg	16 x 50L x 300 Barg	16 x 50L x 300 Barg

(1) Flow specified is at the outlet of the PPNG HE generator measured in Nm³/h at reference conditions: 1 bara and 20°C
(2) For the capacity at higher ambient temperatures please refer to our skid sizing calculator.
(3) 300 Barg skids will be set as standard to 290 Barg off-load pressure.

Options

Pressure regulators

Regulate the stored nitrogen pressure to the required application pressure.

Gas mixers

Allow mixing of nitrogen and oxygen for mixed gas applications.

External room oxygen monitor

Measures the oxygen level in a room to ensure safety.

Additional storage

K6 – 6 x 50L cylinders up to 300 Barg, maximum 90 Nm³ volume
K12 – 12 x 50L cylinders up to 300 Barg, maximum 180 Nm³ volume

K16 – 16 x 50L cylinders up to 300 Barg, maximum 240 Nm³ volume

High ambient temperature version

The unit comes as standard with a connection for an optional oversized refrigerant dryer to be easily connected to allow for reliable operation in temperatures higher than 35°C/95°F.